





35°Diamond Indexable Insert

Profile	Type	Dimension(mm)					Material grade		
		L≈	d	s	d ₁	r	GG03	GG83	
	VBMT110302	11	6.35	3.18	2.8	0.2	●	○	
	VBMT110304					0.4	●	○	
	VBMT110308					0.8	●	○	
	VBMT160404	16.6	9.525	4.76	4.4	0.4	●	○	
	VBMT160408					0.8	●	○	
	VBMT160412					1.2	●	○	
	VBMT110302-GF1	11	6.35	3.18	2.8	0.2	●	○	
	VBMT110304-GF1					0.4	●	○	
	VBMT110308-GF1					0.8	●	○	
	VBMT160404-GF1	16.6	9.525	4.76	4.4	0.4	●	○	
	VBMT160408-GF1					0.8	●	○	
	VBMT110302-GM1	11	6.35	3.18	2.8	0.2	●	○	
	VBMT110304-GM1					0.4	●	○	
	VBMT110308-GM1					0.8	●	○	
	VBMT160404-GM1	16.6	9.525	4.76	4.4	0.4	●	○	
	VBMT160408-GM1					0.8	●	○	
	VBMT160404-GM2	16.6	9.525	4.76	4.4	0.4	●	○	
	VBMT160408-GM2					0.8	●	○	
	VBMT160412-GM2					1.2	●	○	

Shanghai Trisun Parts Manufacture Co.,Ltd.

Head office in Shanghai:

Room 05-06, 16th Floor, Hongjia Building, No.388 Fushan Rd. (Near Xiangcheng Rd.), Pudong, Shanghai, China.

Post Code: 200122

Tel: +86-21-58355541,+86-21-58353145,+86-21-58353343

Fax: +86-21-58353141

E-mail: trisunseal@yahoo.com.cn